



## SAYFA<sup>®</sup> ANCHOR STROP

Sayfa Anchor Point Strops provide improved safety for workmen using a fall arrest harness and lanyard system, at the point of entry to the roof/elevated area. Sayfa Anchor Strops eliminate the need for multiple access anchors, by ensuring the user is in constant restraint at the point of entry to the roof/elevated area, thus limiting any possible fall.

- > Easy and safe operation, fall arrest rated – 15kN
- > Can be custom made to suit a specific length/application
- > Minimises penetrations into roof deck
- > Stainless steel cable, non corrosive

## SPECIFICATION CODE

Sayfa Anchor Point Strop (AP115) – 1000mm to 3000mm

### Specification Summary

Supply and install the proprietary Sayfa Anchor Point Strop as a safe method of providing access onto the roof/elevated area, as per manufacturer, Sayfa Systems, recommendations. Sayfa Stropps to use 316 stainless stranded cable with crimp swage over eyelet. Swage termination to be protected by a plastic shroud to ensure roof deck is not damaged. (Refer instruction manual.)

### System Applications

- > Provides fall protection at the point of entry to roof area for access by maintenance personnel
- > Eliminates pendulum effect ensuring minimal lanyard slack at critical entry point to the roof

### Technical Data

#### Material

Anchor strop – stainless steel (8mm cable)  
Eyelets – stainless steel

#### Dimensions

Strop eyelet diameter – 22mm  
Quicklink – 8mm screw gate type (18mm gate opening)  
Strop lengths – 1000, 2000, 3000mm (eye to eye)  
Custom lengths can be provided to suit application

#### Weight

1000mm – 0.4kg  
2000mm – 0.5kg  
3000mm – 0.7kg

### Working Load Limit

Recommended for single person use – 15kN

- > Support anchor/structure integrity and suitability to be assessed and determined by a competent person prior to installation/use
- > Sayfa Anchor Strop must be used in conjunction with an approved harness and lanyard system certified to AS/NZS1891.1:2007 incorporating an energy absorber where required

### Testing

Testing and performance based on requirements of Australian Standard AS/NZS1891.4:2009.

- > Static load tested – 15kN

### Compliance

Sayfa Anchor Point Strop is designed to comply with Australian Standard AS/NZS1891.4:2009 and relevant statutory OHS Codes of Practice/Guidelines.

### Product Warranty

3 years from date of purchase subject to correct installation, use and maintenance in accordance with manufacturer's specifications and recommendations. (Refer instruction manual.)

### Inspection and Maintenance

Inspection and certification every 12 months by a Height Safety Equipment Inspector in accordance with manufacturer's specifications and requirements of Australian Standard AS/NZS1891.4:2009 Section (9). (Refer instruction manual.)

### Important Note

Failure to supply and/or install proprietary product in accordance with above standards and codes, specifications and instructions voids complete system certification and/or warranty.

### Technical Support

#### Sayfa Systems

T \ 1300 301 755  
F \ 1300 881 092  
E \ [technical@sayfa.com.au](mailto:technical@sayfa.com.au)  
W \ [www.sayfa.com.au](http://www.sayfa.com.au)

*Designed and manufactured by Sayfa Systems  
22.03.2011*