



STEALTH™ SURFACE MOUNT ANCHOR POINT

The Stealth Permanent Anchor Point is ideally suited to maintenance personnel working at heights utilising a harness and lanyard fall protection system. The 15kN rated Stealth Anchor Point incorporates unique energy absorbing properties allowing fixture to lighter structures and roof decks.

- > One piece precision folded unit
- > Multiple fixing locations suit surface mounting to varying roof deck profiles
- > Simple, quick installation
- > Can be used in any direction
- > No on site assembly required
- > Unobtrusive, easily powdercoated to blend in with surroundings

SPECIFICATION CODE

Stealth Anchor (AP135)

Specification Summary

Supply and install the proprietary Stealth Anchor Point, as per manufacturer, Sayfa Systems, recommendations. Stealth Anchor Point to be one piece, profiled stainless steel plate and to incorporate a series of fixing holes to ensure secure fixture utilising construction grade Bulbrite rivets and Tek screw fixings. Exact anchor location and fixing method to be determined by competent person at time of installation. (Refer instruction manual.)

System Applications

- > Ideally suited as a permanent anchorage point for personnel working at heights, utilising a harness and lanyard fall protection system
- > Used and set up to prevent access beyond the fall edge
- > Ideal for – general roof and gutter maintenance
- > For access and fall protection to roof mounted plant and equipment

Technical Data

Material

Profiled stainless steel

Dimensions

290 mm (L) x 260 mm (W) x 55 mm (H)

Weight

0.97 kg (excluding fixings)

Fixings

Timber fixing – 14g/75mm type 17 Tek screws
Metal fixing – 14g/75mm self drilling Tek screws
Metal roof deck fixing – 8mm construction grade Bulbrite rivets (Refer instruction manual.)

Working Load Limit

- Recommended for single person use – 15 kN rated.
- > Support structure integrity, suitability and fixing method to be assessed and determined by a competent person prior to installation
 - > Stealth Anchor Point must be used in conjunction with an approved harness and lanyard system incorporating an energy absorber

Compliance

Stealth Anchor Point is designed and manufactured generally in accordance with requirements of Australian Standard AS/NZS 1891.4:2009 and relevant statutory OHS Codes of Practice/Guidelines.

Testing

- Testing and performance based on requirements of Australian Standard AS/NZS 1891.4:2009.
- > Dynamic load tested – 15kN
 - Resultant load on structure – 8.7kN

Product Warranty

3 years from date of purchase subject to correct installation, use and maintenance in accordance with manufacturer's specifications and recommendations. (Refer instruction manual.)

Inspection and Maintenance

Inspection and certification every 12 months by competent person in accordance with manufacturer's specifications and requirements of Australian Standard AS/NZS 1891.4:2009 Section (9). (Refer instruction manual.)

Important Note

Failure to supply and/or install proprietary product in accordance with above standards and codes, specifications and instructions voids complete system certification and/or warranty.

Technical Support

Sayfa Systems

T \ 1300 301 755

F \ 1300 881 092

E \ technical@sayfa.com.au

W \ www.sayfa.com.au

Designed and manufactured by Sayfa Systems